
product information

KHS Innocoll DP 1600





*example illustration

product characteristics

adhesives for labeling

- based on casein and dispersion
- for glas / varnished surfaces
- for metal surfaces
- suitable for labelling glass containers and their lids to stick
- 🖌 for extrem conditions
- raw materials correspond to the FDA Directives 21 CFR 175.
 105.

The product is a glue with a good adhesion towards glass, varnished surfaces and other difficult surfaces, e. g. PET. The adhesive is suitable for labelling glass containers and their lids to stick the security labels and Tax Bands (spirits) or for labelling varnished materials (cans). The product is also usable for applying paper labels on PET bottles even under extrem conditions.

application notes

The temperature processing range is 20 - 30 °C, ideal at 25 °C. Before a different adhesive is to be used on the machine, it must be cleaned carefully.

18

storage

The product can be stored in its original sealed container for at least 6 months at room temperature after date of production - but not below +4 °C.

301244607150

characteristics	Innocoll DP 1600	
viscosity, dyn.	50.000±15.000 mPas	
colour	beige-transparent	
pH value	9,5 ± 0,2	
density	1,02 ± 0,03 g/cm3	
container	packing size	material number

33 kg

To the best of our knowledge and experience, the data / information we have provided is reliable but it does not amount to a statement of assured properties in the context of the latest regulations issued by the Federal Court of Justice. With regard to the many options available in terms of alternative applications and operating conditions the data / information can only be regarded as of a non-binding nature. In each separate case it is necessary for you to carry out your own trials before large-scale use although, of course, in that respect our application technology is available to you upon request.